4-Load professional

Chargers



The recently developed 4Load Professional chargers round off the 4Load programme.

Superior flexibility in terms of setting options ensure the perfect load profile for any type of lead-based battery, thus optimising battery life.

The product series furthermore features user-friendly operation via the display, and comprehensive safety extras. The devices are additionally equipped with an automatic charge retention.





www.4load.de

Item no.	Туре	Amperage	Voltage	Dimensions mm L x W x H	Quantity
CB-P10	ChargeBox P10	10 A or 5 A	12 V or 24 V	271 x 135 x 82	
CB-P20	ChargeBox P20	20 A or 10 A	12 V or 24 V	271 x 135 x 82	

Product line: 12V / 24 V 4Load professional chargers

Model: Primarily clocked charger, selection of the correct

charging program

Safety: Reverse battery protection, short circuit-proof,

Protective system: IP33

Battery types: Lead/acid batteries, gel batteries, AGM batteries,

SLA batteries

Charger

characteristic: Iul.oU, IU.oU, IUU.oU charger characteristic

Accessories: Case

Properties: LED charging status display (red + yellow + green)

Display: two-line display

> Before starting the charging process: Selection of relevant voltage + amperage + load curve (stored

previous setting)

> during the charging status: charging status dis-

play + current information

Charging options: P10: 12 V/5 A + 12 V/10 A + 24 V/5 A + 24 V/10 A

P20: 12 V/15 A + 12 V/20 A + 24 V/15 A + 24 V/20 A

4 selectable charging curves:

> Standard for passenger cars/trucks

(battery also in the vehicle)

> Wet (cyclic applications)

> Gel (cyclic applications)

> AGM / Odyssey (cyclical applications)

Automatic charge maintenance

Use: passenger cars – trucks – tractors – buses –

construction equipment – rehab vehicles – boats

