




S12-128 AGM


Rolls 12V 115Ah (C20) Deep Cycle AGM Battery




CONSTANT CURRENT DISCHARGE (AMPS)									
CUT OFF VOLTAGE V/CELL	30M	45M	1HR	2HR	3HR	5HR	8HR	10HR	20HR
1.75V	98	72	59.7	31.6	23.8	16.7	11.4	9.90	5.75

RESERVE CAPACITY		CCA	
@25AMPS	@75 AMPS	CCA@0°C	CCA@-18°C
165 Mins.	45 Mins.	720	605

SPECIFICATIONS		
Nominal Voltage		12 Volt
Rated Capacity (20 hour rate)		115Ah
Dimensions	Height	236mm
	Length	328mm
	Width	172mm
Weight		33 Kg



CHARACTERISTICS		
Capacity 77°F (25°C)	100 Hour Rate	128Ah
	20 Hour Rate	115Ah
	10 Hour Rate	104Ah
Internal Resistance	Full charged Battery 77°F (25°C)	3.8mΩ
Capacity Affected by Temperature (20hr rate)	104°F (40°C)	102%
	77°F (25°C)	100%
	32°F (0°C)	85%
Self Discharge 77°F (25°C)	5°F (-15°C)	65%
	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
Max Discharge 77°F (25°C)	Capacity after 12 month storage	64%
		1100A (5s)
Terminal	Standard	M8-TP08
Charging (Constant Voltage)	Cycle	14.5 to 14.9V DC/unit Average at 25°C
	Float	13.6 to 13.8V DC/unit Average at 25°C



This information is generally descriptive only and is not intended to make or imply and representation, guarantee or warranty with respect to any cells and batteries. Call and battery design/specifications are subject to modifications without notice. For further information contact Rolls Battery Europe.

